

产品规格书

产品名称	单刀十六掷开关		规格型号	HTSA16-01403																																				
技术指标	1	工作频率	1~40GHz																																					
	2	插入损耗	≤12dB																																					
	3	驻波	≤2																																					
	4	开关隔离	≥60dB																																					
	5	承受功率	≥20dBm																																					
	6	开关时间	≤300ns																																					
	7	工作方式	吸收式																																					
电源及控制	1	电源	~220V 交流电																																					
	2	控制	4 位 TTL 电平																																					
接口形式	1	射频接口	2.92mm-K																																					
	2	控制	J30J-9ZKP, 接口定义待定																																					
外形尺寸	19 英寸 1U 标准机箱																																							
温度环境	1	工作温度	-20~+70℃																																					
	2	存储温度	-40~+85℃																																					
真值表	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>C4</th> <th>C3</th> <th>C2</th> <th>C1</th> <th>功能</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>XS01 与 XS02 导通</td> </tr> <tr> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td>XS01 与 XS03 导通</td> </tr> <tr> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td>XS01 与 XS04 导通</td> </tr> <tr> <td>....</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td>1</td> <td>1</td> <td>0</td> <td>XS01 与 XS16 导通</td> </tr> <tr> <td>1</td> <td>1</td> <td>1</td> <td>1</td> <td>XS01 与 XS17 导通</td> </tr> </tbody> </table>					C4	C3	C2	C1	功能	0	0	0	0	XS01 与 XS02 导通	0	0	0	1	XS01 与 XS03 导通	0	0	1	0	XS01 与 XS04 导通					1	1	1	0	XS01 与 XS16 导通	1	1	1	1	XS01 与 XS17 导通
	C4	C3	C2	C1	功能																																			
	0	0	0	0	XS01 与 XS02 导通																																			
	0	0	0	1	XS01 与 XS03 导通																																			
	0	0	1	0	XS01 与 XS04 导通																																			
																																							
	1	1	1	0	XS01 与 XS16 导通																																			
1	1	1	1	XS01 与 XS17 导通																																				