


产品规格书

产品名称	单刀四掷开关		规格型号	HTSR4-02402																									
技术指标	1	工作频率	0.2~4GHz																										
	2	插入损耗	≤1.5dB																										
	3	驻波	≤1.3																										
	3	各路幅度一致性	≤±0.5dB																										
	4	开关隔离	≥70dB																										
	5	承受功率	≥1W																										
	6	开关时间	≤200nS																										
7	工作方式	反射式																											
电源及控制	1	电源	+5V/260mA& -5V/50mA																										
	2	控制	4 位 TTL 电平																										
接口形式	1	射频接口	SMA-K																										
	2	控制及电源	J30J-9ZKP 1—+5V, 2—GND, 3—空, 4—-5V, 5—GND, 6—TTL0, 7—TTL1, 8—TTL2, 9—TTL3																										
外形尺寸	 <p>表面处理：本色导电氧化 产品标识：刻字，宋体，字高 2mm</p>																												
温度环境	1	工作温度	-40~+70℃																										
	2	存储温度	-55~+85℃																										
真值表	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>TTL3</th> <th>TTL2</th> <th>TTL1</th> <th>TTL0</th> <th>功能</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td>J0 与 J1 导通</td> </tr> <tr> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td>J0 与 J2 导通</td> </tr> <tr> <td>0</td> <td>1</td> <td>0</td> <td>0</td> <td>J0 与 J3 导通</td> </tr> <tr> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>J0 与 J4 导通</td> </tr> </tbody> </table>				TTL3	TTL2	TTL1	TTL0	功能	0	0	0	1	J0 与 J1 导通	0	0	1	0	J0 与 J2 导通	0	1	0	0	J0 与 J3 导通	1	0	0	0	J0 与 J4 导通
TTL3	TTL2	TTL1	TTL0	功能																									
0	0	0	1	J0 与 J1 导通																									
0	0	1	0	J0 与 J2 导通																									
0	1	0	0	J0 与 J3 导通																									
1	0	0	0	J0 与 J4 导通																									